

## 17 - Rear Suspension/Technical Specifications

## TORQUE SPECIFICATIONS

DESCRIPTION	N·m	Ft. Lbs.	In. Lbs.	COMMENT
Camber Link to Knuckle Mounting Bolt	65 Plus 90°	48 Plus 90°	—	* <b>NEW FASTENER:</b> Do not reuse these fasteners. If removed, a new fastener must be installed and tightened to specifications.
Camber Link to Crossmember Mounting Bolt	65 Plus 90°	48 Plus 90°	—	* <b>NEW FASTENER:</b> Do not reuse these fasteners. If removed, a new fastener must be installed and tightened to specifications.
Hub Nut	71 Plus 47°	52 Plus 47°	—	* <b>NEW FASTENER:</b> Do not reuse these fasteners. If removed, a new fastener must be installed and tightened to specifications.
Hub and Bearing to Knuckle Mounting Bolts	100	74	—	
Lower Control Arm to Crossmember Bolt – Front	200	148	—	* <b>NEW FASTENER:</b> Do not reuse these fasteners. If removed, a new fastener must be installed and tightened to specifications.
Lower Control Arm to Crossmember Bolt – Rear	60 Plus 180°	44 Plus 180°	—	* <b>NEW FASTENER:</b> Do not reuse these fasteners. If removed, a new fastener must be installed and tightened to specifications.
Lower Control Arm to Knuckle Bolt	110 Plus 180°	81 Plus 180°	—	* <b>NEW FASTENER:</b> Do not reuse these fasteners. If removed, a new fastener must be installed and tightened to specifications.
Shock Absorber to Lower Control Arm Mounting Bolt	60 Plus 180°	44 Plus 180°	—	* <b>NEW FASTENER:</b> Do not reuse these fasteners. If removed, a new fastener must be installed and tightened to specifications.
Shock Absorber to Body Mounting Bolts	26	19	—	

DESCRIPTION	N·m	Ft. Lbs.	In. Lbs.	COMMENT
Stabilizer Bar to Crossmember Bolts	20	15	—	
Stabilizer Bar Link to Stabilizer Bar Nut	100	74	—	* <b>NEW FASTENER:</b> Do not reuse these fasteners. If removed, a new fastener must be installed and tightened to specifications.
Stabilizer Bar Link to Lower Control Nut	100	74	—	* <b>NEW FASTENER:</b> Do not reuse these fasteners. If removed, a new fastener must be installed and tightened to specifications.
Toe Link to Crossmember Mounting Bolt	65 Plus 90°	48 Plus 90°	—	* <b>NEW FASTENER:</b> Do not reuse these fasteners. If removed, a new fastener must be installed and tightened to specifications.
Toe Link to Knuckle Mounting Nut	120	89	—	